

EMULATOR 4 ULTRAS

COMPARISON CHART



	E4XT Ultra	E-Synth Ultra	E6400 Ultra	E5000 Ultra
Polyphony	128 voices	64 voices (expandable to 128)	64 voices (expandable to 128)	64 voices (not expandable)
RAM	64 MB (expandable to 128)	16 MB (expandable to 128)	16 MB (expandable to 128)	4 MB (expandable to 128)
Hard Drive	3.2 GB	None (can be installed with Option 6301 for SCSI or 6303 for IDE)	None (can be installed with Option 6301 for SCSI or 6303 for IDE)	None (can be installed with Option 6301 for SCSI or 6303 for IDE)
Dual MIDI	32 channels	32 channels	No (can be installed with Option 6862)	No (can be installed with Option 6862)
Stereo-Effects Processor	24-bit	24-bit	24-bit	24-bit
Balanced Analog Outputs	8 (expandable to 16)	8 (expandable to 16)	8 (expandable to 16)	4 (expandable to 12)
Word Clock & AES/EBU I/O	Yes	Yes	No (can be installed with Option 6862)	No (can be installed with Option 6862)
RISC Processor	Ultra-fast 32-bit	Ultra-fast 32-bit	Ultra-fast 32-bit	Ultra-fast 32-bit
EOS 4.01 Software	Yes	Yes	Yes	Yes
CD-ROMs	9	9	9	2
16 MB Internal ROM	No (can be added with	Yes	No (can be added with	

EMULATOR 4 ULTRAS

OPTIONS COMPARISON CHART



	E4XT Ultra	E-Synth Ultra	E6400 Ultra	E5000 Ultra
6860 128 Voice Polyphony	Standard	Optional	Optional	Not Available
6861 16 Out / 8 In A-DAT	Optional	Optional	Optional	Optional
6862 D-WAM	Standard	Standard	Optional	Optional
6865 2nd SCSI Port	Optional	Optional	Optional	Optional
6870 E-Synth 16 MB Sound ROM	Optional	Standard	Optional	Optional
6871 Orbit / Phatt Sessions 16 MB Sound ROM	Optional	Optional	Optional	Optional
6876 16 MB Flash ROM	Optional	Optional	Optional	Optional
6301 (for SCSI drives)	Hard-Drive Standard	Optional	Optional	Optional
6303 (for IDE drives)	Hard-Drive	Optional	Optional	Optional
6313 8 Analog Output Expander	Optional	Optional	Optional	Optional