



## Technical Specifications



## XENYX 1202FX

Premium 12-Input 2-Bus Mixers with XENYX Mic Preamps,  
British EQs and Multi-FX Processor

# XENYX 1202FX

## Premium 12-Input 2-Bus Mixer with XENYX Mic Preamps, British EQs and Multi-FX Processor

- Premium ultra-low noise, high headroom analog mixer
- 4 state-of-the-art XENYX Mic Preamps comparable to stand-alone boutique preamps
- Neo-classic "British" 3-band EQs for warm and musical sound
- Studio-grade stereo FX processor with 100 awesome presets including reverb, chorus, flanger, delay, pitch shifter and various multi-effects
- FX send control per channel for internal FX processor and/or as external send
- Main mix outputs plus separate control room, phones and stereo CD/tape outputs
- CD/tape inputs assignable to main mix or control room/phones outputs
- Long-wearing 60-mm logarithmic-taper fader and sealed rotary controls
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

## Specifications

### Mono Inputs

#### Microphone Inputs

Type	XLR, electronically balanced, discrete input circuit
------	--

#### Mic E.I.N. (20 Hz - 20 kHz)

@ 0 $\Omega$ source resistance	-132.7 dB / 137 dB A-weighted
@ 50 $\Omega$ source resistance	-130 dB / 133.9 dB A-weighted
@ 150 $\Omega$ source resistance	-127.1 dB / 130.9 dB A-weighted
Frequency response	<10 Hz - 200 kHz (-1 dB)
Gain range	+10 to +60 dB
Max. input level	+12 dBu @ +10 dB gain
Impedance	approx. 2.6 k $\Omega$ balanced
Signal-to-noise ratio	-107 dB / -111 dB A-weighted (0 dBu In @ +22 dB gain)
Distortion (THD + N)	0.005% / 0.003% A-weighted

#### Line Input

Type	¼" TRS connector electronically balanced
Impedance	approx. 20 k $\Omega$ balanced approx. 10 k $\Omega$ unbalanced
Gain range	-10 to +40 dB
Max. input level	+20 dBu @ 0 dB Gain

#### Fade-Out Attenuation<sup>1</sup> (Crosstalk Attenuation)

Main fader closed	85 dB
Channel fader closed	88 dB

### Frequency Response

#### Microphone Input to Main Out

<10 Hz - 80 kHz	+0 dB / -1 dB
<10 Hz - 137 kHz	+0 dB / -3 dB

#### Stereo Inputs

Type	¼" TRS connector, electronically balanced
Impedance	approx. 20 k $\Omega$ bal. / 10 k $\Omega$ unbal. (+4 dBu operating level) approx. 20 k $\Omega$ bal. / 5 k $\Omega$ unbal. (-10 dBV)
Max. input level	+22 dBu

#### EQ Mono Channels

Low	80 Hz / $\pm$ 15 dB
Mid	2.5 kHz / $\pm$ 15 dB
High	12 kHz / $\pm$ 15 dB

**Audio Outputs****FX Send**

Type	¼" TRS connector, unbalanced
Impedance	approx. 120 Ω
Max. output level	+22 dBu

**Main Outputs**

Type	¼" TRS connector, unbalanced
Impedance	approx. 120 Ω
Max. output level	+22 dBu

**Control Room Outputs**

Type	¼" TRS connector, unbalanced
Impedance	approx. 120 Ω
Max. output level	+22 dBu

**Headphones Output**

Type	¼" TRS connector, unbalanced
Max. output level	+19 dBu / 150 Ω (+25 dBm)

**Main Mix System Data<sup>2</sup>****Noise**

Main mix @ -∞, Channel fader -∞	-105 dB / -108 dB A-weighted
Main mix @ 0 dB, Channel fader -∞	-94 dB / -97 dB A-weighted
Main Mix @ 0 dB, Channel fader @ 0 dB	-83 dB / -85 dB A-weighted

**FX Section**

Converter	24-bit Sigma-Delta
Sampling rate	40 kHz

**Mains Voltage**

USA/Canada	120 V~, 60 Hz, MXUL6 adapter
U.K./Australia	240 V~, 50 Hz, MXUK6 adapter
Europe	230 V~, 50 Hz, MXEU6 adapter
China/Korea	220 V~, 50 Hz, MXCN6 adapter
Japan	100 V~, 60 Hz, MXJP6 adapter
Output	2 x 14.8 V~, 2 x 500 mA

**Dimensions****1202FX**

Dimensions (H x W x D)	1 ½ x 9 ½ x 8 ¾" 47 x 220 x 242 mm
Weight (Net)	approx. 4.6 lbs / 2.1 kg

## Measuring conditions:

- 1 kHz rel. to 0 dBu; 20 Hz - 20 kHz; line input; main output; unity gain.
- 20 Hz - 20kHz; measured at main output. Channels 1 - 4 unity gain; EQ flat; all channels on main mix; channels 1/3 as far left as possible, channels 2/4 as far right as possible. Reference = +6 dBu.

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER, KLARK TEKNIK, MIDAS, BUGERA, AND TURBOSOUND ARE PART OF THE MUSIC GROUP (MUSIC-GROUP.COM). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HEREIN. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP AND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTAKING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED.

© 2013 MUSIC Group IP Ltd. Trident Chambers, Wickhams Cay, P.O. Box 146, Road Town, Tortola, British Virgin Islands